

## WEDGE Mounting Set for Altitrack

### Mounting Set comprises of:

- Front Loop with retainer hook, black webbing, 12 mm wide x 25 mm long
- Bungee cord (black), Ø 2,5 x 250 mm
- Self-blocking Cord-Lock (black), Ø 26 x 8 mm
- Left-Side Loop with female side squeeze buckle, black webbing, 12 mm wide x 68 mm long
- Right-Side Loop with male side squeeze buckle, black webbing, 12 mm wide x 48 mm long



### Installation:

- Remove ALL straps from the Altitrack.
- Slip the Front Loop from the top through the front slot hole in the Altitrack. The webbing hook will prevent the loop to be pulled through the slot.
- Route the Bungee Cord through the loop-end of the Front Loop.
- Place the Altitrack onto the WEDGE and route the two Bungee Cord ends through the Cord-Lock, which must be placed underneath the Wedge supporting area. To widen the Cord-Lock, push the spring powered lever on the Cord-Lock downwards.
- Slip the Left-Side Loop (with female side squeeze buckle) from the bottom through the slot hole on the left side of the Altitrack.
- Pull the actual loop all the way through the left slot hole and slip the female buckle through the loop.
- Then pull the buckle down until the sling-knot over the slot hole is tight.
  
- Slip the Right-Side Loop (with male side squeeze buckle) from the bottom through the slot hole on the right side of the Altitrack.
- Pull the actual loop all the way through the right slot hole and slip the male buckle through the loop.
- Then pull the buckle down until the knot over the slot hole is tight.
- Put the two side squeeze buckles underneath the Wedge support area together, while using the little webbing tabs for proper aligning of the two buckle sides.
- Tighten the Bungee-Cord by pulling the two Bungee ends through the Cord-Lock.
- Make a tight safety knot on the two Bungee ends
- DONE



**Before each jump, make sure that all components of this set, the Wedge and the Altitrack have a tight and proper fit and that no wear and tear has occurred.**

### Adjusting the Altitrack:

- Undo the side squeeze buckle underneath the Wedge support area.
- Flip the Altitrack over (it is now only held by the Bungee-Cord).
- Make your adjustments / readings.
- Flip the Altitrack back onto the Wedge.
- Put the male and female buckles underneath the Wedge support area together again.

